

TECHNICAL DATA

GENERAL INFORMATION	TECHNICAL INFORMATION	TEST METHOD	APPLICATIONS
MATERIAL: AMAZON FLOWER	COMPRESSIVE STRENGTH:	142.60 N/mm ²	RESIDENTIAL <input checked="" type="checkbox"/>
MATERIAL TYPE: GRANITE	WATER ABSORPTION:	0.06%	COMMERCIAL <input checked="" type="checkbox"/>
ORIGIN: BRAZIL	BULK DENSITY:	2,669 kg/dm ³	LIGHT TRAFFIC <input checked="" type="checkbox"/>
QUARRY PRODUCTIVITY:	ULTIMATE TENSILE STRENGTH:		HEAVY TRAFFIC <input checked="" type="checkbox"/>
POOR <input type="checkbox"/>	COEFF. THERMAL EXPANSION:		WET AREAS <input checked="" type="checkbox"/>
ADEQUATE <input type="checkbox"/>	FRICTIONAL WEAR:	0.57 mm	INDOOR FLOORING <input checked="" type="checkbox"/>
GOOD <input checked="" type="checkbox"/>	BENDING TENSILE STRENGTH:	14.86 N/mm ²	OUTDOOR FLOORING <input checked="" type="checkbox"/>
EXCELLENT <input type="checkbox"/>	AFTER FREEZING:		INDOOR COVERING (WALLS) <input checked="" type="checkbox"/>
			OUTDOOR COVERING (WALLS) <input checked="" type="checkbox"/>
			INDOOR COUNTERTOP (VANITIES) <input checked="" type="checkbox"/>
			OUTDOOR COUNTERTOP <input checked="" type="checkbox"/>
			SWIMMING POOL FLOORING AND COVERING <input checked="" type="checkbox"/>