

TECHNICAL DATA

GENERAL INFORMATION	TECHNICAL INFORMATION	TEST METHOD	APPLICATIONS
MATERIAL: KASHMIR GOLD	COMPRESSIVE STRENGTH:	1578 kg/cm ²	RESIDENTIAL <input checked="" type="checkbox"/>
MATERIAL TYPE: GRANITE	WATER ABSORPTION:	0.38%	COMMERCIAL <input checked="" type="checkbox"/>
ORIGIN: INDIA	BULK DENSITY:	2682 kg/m ³	LIGHT TRAFFIC <input checked="" type="checkbox"/>
QUARRY PRODUCTIVITY:	ULTIMATE TENSILE STRENGTH:	104 kg/cm ²	HEAVY TRAFFIC <input checked="" type="checkbox"/>
POOR <input type="checkbox"/>	COEFF. THERMAL EXPANSION:	0.0013 mm/mm ^o C	WET AREAS <input checked="" type="checkbox"/>
ADEQUATE <input type="checkbox"/>	FRICTIONAL WEAR:		INDOOR FLOORING <input checked="" type="checkbox"/>
GOOD <input checked="" type="checkbox"/>	IMPACT TEST/MIN. FALL HEIGHT:	41 cm	OUTDOOR FLOORING <input checked="" type="checkbox"/>
EXCELLENT <input type="checkbox"/>	AFTER FREEZING:	1599 kg/cm ²	INDOOR COVERING (WALLS) <input checked="" type="checkbox"/>
			OUTDOOR COVERING (WALLS) <input checked="" type="checkbox"/>
			INDOOR COUNTERTOP (VANITIES) <input checked="" type="checkbox"/>
			OUTDOOR COUNTERTOP <input checked="" type="checkbox"/>
			SWIMMING POOL FLOORING AND COVERING <input checked="" type="checkbox"/>