

## TECHNICAL DATA

GENERAL INFORMATION	TECHNICAL INFORMATION	TEST METHOD	APPLICATIONS
<b>MATERIAL:</b> LABRADORITE BIANCA	<b>COMPRESSIVE STRENGTH:</b>	2250 kg/cm <sup>2</sup>	RESIDENTIAL <input checked="" type="checkbox"/>
<b>MATERIAL TYPE:</b> GRANITE	<b>WATER ABSORPTION:</b>	0.12%	COMMERCIAL <input checked="" type="checkbox"/>
<b>ORIGIN:</b> MADAGASCAR	<b>BULK DENSITY:</b>	2740 kg/m <sup>3</sup>	LIGHT TRAFFIC <input checked="" type="checkbox"/>
<b>QUARRY PRODUCTIVITY:</b>	<b>ULTIMATE TENSILE STRENGTH:</b>	201 kg/cm <sup>2</sup>	HEAVY TRAFFIC <input checked="" type="checkbox"/>
POOR <input type="checkbox"/>	<b>COEFF. THERMAL EXPANSION:</b>	0.0051 mm/mm <sup>o</sup> C	WET AREAS <input checked="" type="checkbox"/>
ADEQUATE <input type="checkbox"/>	<b>FRICTIONAL WEAR:</b>	0.75 mm	INDOOR FLOORING <input checked="" type="checkbox"/>
GOOD <input checked="" type="checkbox"/>	<b>IMPACT TEST/MIN. FALL HEIGHT:</b>	46 cm	OUTDOOR FLOORING <input checked="" type="checkbox"/>
EXCELLENT <input type="checkbox"/>	<b>AFTER FREEZING:</b>	1969 kg/cm <sup>2</sup>	INDOOR COVERING (WALLS) <input checked="" type="checkbox"/>
			OUTDOOR COVERING (WALLS) <input checked="" type="checkbox"/>
			INDOOR COUNTERTOP (VANITIES) <input checked="" type="checkbox"/>
			OUTDOOR COUNTERTOP <input checked="" type="checkbox"/>
			SWIMMING POOL FLOORING AND COVERING <input checked="" type="checkbox"/>